


## 29 229 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES



### PRODUCT DESCRIPTION

- Colour: chrome
- final installation set for
- GROHE Rapido SmartBox (35 602 000)
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non-return valves and dirt strainers
- multiple outlets can be run simultaneously
- without floor installation plate
- flow performance: outlet B = 24 l/min outlet C = 26 l/min outlet B+C = 29 l/min

## 29 229 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES



### SPARE PARTS, June 2018 – now

- 1: Ball seal dia. 9x6.8 mm (Order-nr. 48360000)
- 2: Non-return valves (Order-nr. 47979000)
- 3: Thermostatic compact cartridge 3/4" (Order-nr. 49028000)
- 4: Cartridge (Order-nr. 48359000)
- 5: Push button (Order-nr. 48361000)
- 5.1: pushbutton (Order-nr. 14077000)
- 6: Temperature control handle (Order-nr. 49029000)
- 6.1: Cap (Order-nr. 1015030000)
- 6.2: handle adaptor (Order-nr. 1015059990)
- 7: Mounting plate (Order-nr. 48363000)
- 8: Socket spanner (Order-nr. 49059000)\*
- 9: GROHE TurboStat cartridge 3/4" (Order-nr. 49003000)\*
- 10: Backflow protection combination (EN1717) (Order-nr. 14055000)\*
- 11: Service stops (Order-nr. 1405300M)\*
- 12: Universal extension set single-lever mixers, 25 mm (Order-nr. 14048000)\*

\* Optional accessories